



## API CI-4/SL 15W-40 Motor Oil

Dura Flow™ API CI-4 PLUS/SL 15W-40 Motor Oil is a high-quality universal fleet engine oil designed for use in on-highway diesel trucks and off-highway diesel equipment, as well as in passenger cars and light trucks with either gasoline or diesel engines. It provides excellent protection for gasoline engines used in mixed commercial fleets.

Dura Flow™ API CI-4 PLUS/SL 15W-40 Motor Oil also meets or exceeds requirements of performance specifications for:

- API CI-4 PLUS, CI-4, CH-4, SL
- Cummins CES 20078
- Mack EO-N Premium Plus 03
- Volvo VDS-2
- Caterpillar ECF-2, ECF-1a

Dura Flow™ API CI-4 PLUS/SL 15W-40 Motor Oil is formulated with advanced additive technology. This provides excellent wear protection, soot control and bearing corrosion protection. In addition, it has excellent soot dispersancy, which provides protection against abrasive wear and oil thickening caused by soot. It also minimizes deposit formation, due to its excellent resistance to oxidation.

Always follow manufacturer's recommendations for API quality and drain intervals.

### Typical Properties:

|   |          |
|---|----------|
| Product: Dura Flow™ API CI-4 PLUS/SL 15W-40 motor oil |          |
| SAE Viscosity Grade                                   | 15W-40   |
| API Classification                                    | CI-4+/SL |
| Product Code  | 5008     |
| Kinematic Viscosity @ 100oC, cSt (ASTM D-445)         | 15.0     |
| Kinematic Viscosity @ 40oC, cSt (ASTM D-445)          | 113.0    |
| Viscosity Index (ASTM D-2270)                         | 138      |
| Total Base Number (ASTM D-2896)                       | 9.5      |
| API Gravity (ASTM D-1298)                             | 29.7     |
| Sulfated Ash (ASTM D-874) wt %                        | 1.18     |