



## EP-2 Lithium Complex Grease

**Dura Flow™ EP-2 Lithium Complex Grease** is multi-purpose lubricating grease designed to withstand extreme temperatures because of its high dropping point and natural oxidation inhibition.

**Dura Flow™ EP-2 Lithium Complex Grease** is formulated from high quality base stocks, corrosion inhibitors, and antioxidants to prevent wear and give it added stability in extreme service conditions.

**Dura Flow™ EP-2 Lithium Complex Grease** is recommended for use in wheel bearings, axles, ball joints, on/off road applications and power takeoffs.

### Typical Properties

NLGI Grade	2
Thickener Type	Lithium Complex
Color	Red
Texture	Buttery
Appearance	Smooth
Operating Temperature Range	-40°F to +325°F

Penetration	ASTM D 217	
Worked 60 Strokes		265-295
Dropping Point, °F (°C)	ASTM D 2265	500 (260)
Oil Separation, % Loss	ASTM D 1742	2.5
4 Ball Wear Test, mm Scar Diameter	ASTM D 2266	0..55
4 Ball E.P. Weld Point, Kg	ASTM D 2596	250
4 Ball Load Wear Index, Kgf	ASTM D 9596	45
Water Washout, % Loss	ASTM D 1264	4.5
Timken, 0 K load, Lb.	ASTM D 2509	50
Rust Prevention, Rating	ASTM D 1743	Pass
Oxidation, Stability, PSI Drop	ASTM D 942	5
Wheel Bearing Leakage, grams, Loss	ASTM D 4290	6.0
Copper Corrosion, Rating	ASTM D 4048	1b
Base Oil Characteristics	ASTM D 445	
Viscosity @ 40°C cSt		140-180
Viscosity @ 100°C cSt		13.5-16.5
Viscosity Index, Min		90