



SAE 50 Synthetic Manual Transmission Fluid

Dura Flow™ SAE 50 Synthetic Manual Transmission Fluid is a non-EP synthetic extended drain transmission fluid in on- and off-road equipment transmissions. Dura Flow™ SAE 50 Synthetic Manual Transmission Fluid uses field-proven additive technology that demonstrates outstanding wear protection and oxidation stability. With demonstrated field trial performance, this synthetic transmission fluid is suitable for use in 500,000 mile drain heavy duty transmission service.

Dura Flow™ SAE 50 Synthetic Manual Transmission Fluid is suitable for use where the following equipment requirements are specified:

- Mack TO-A Plus
- Eaton Roadranger PS-081
- ArvinMeritor O-81
- Navistar TMS-6816
- Eaton PS-164 Rev.7
- API MT-1
- API GL-1

Always follow manufacturers' recommendations for specification and viscosity requirements.

Typical Properties:

Product: Dura Flow™SAE 50 Synthetic Manual Transmission Fluid	
Product Code	5015
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	21.5
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	156.3
Viscosity Index (ASTM D-2270)	163
API Gravity (ASTM D-1298)	31.9